


3M™ Twin Axial Cable SL8800 Series

30 AWG 100 ohm Internal Cable



*Example Construction above – see drawings for specific constructions and product dimensions

Physical Description

Signal Pair Construction

| | |
|-----------------------------|--|
| Wire | 30 AWG Solid Copper - Silver or Tin Plated |
| Insulation | Solid Polyolefin (natural color) |
| Wire/Insulated Diameter ... | 0.25/0.79 mm |

Auxiliary Signal Lines (if included)

| | |
|-----------------------------|----------------------------------|
| Wire | 30 AWG Solid Copper Tin Plated |
| Insulation | Solid Polyolefin (natural color) |
| Wire/Insulated Diameter ... | 0.25/0.56 mm |

| | |
|----------------------|---|
| Ground Wire | 30 AWG • Solid Copper Tin Plated or 32 AWG • Stranded 7/40 Copper Tin Plated |
| Primary Shield | Aluminum/Polyester at 0.022 mm total thickness • Aluminum In Longitudinal Construction • 100% Coverage |

| | |
|--------------------------------|--|
| Approvals and Compliance | UL AWM Style 21008 File E42769 -20°C to 80°C • 150V • Horizontal Flame RoHS Compliant (see back) • Halogen Free (see back) |
|--------------------------------|--|

| | |
|---------------------|---|
| Cable Marking | 3M (<i>Part Number</i>) 30 AWG (<i>Signal Plating</i>) (<i>Lot</i>) |
| Example | 3M SL8801/12-10DA5-00 30 AWG Silver TW602-1 |

Electrical Properties (Signal Pairs)

| | |
|----------------------------------|---------------------|
| Impedance | 100 +/- 5 ohms |
| Capacitance | 50 pF/m (Typical) |
| Propagation Delay | 4.95 ns/m (Typical) |
| Intrapair Skew (TDT 3m)..... | <10 ps/m |
| Withstanding Voltage | 1500 V |
| Insulation Resistance | 1000 Megohms |
| Conductor Resistance (max) | 370 Ω/km |
| Attenuation (typical) | Resonance-Free |

| Frequency (GHz) | 0.5 | 1.0 | 2.0 | 5.0 | 10.0 | 15.0 | 20.0 |
|-----------------------|-------|------|------|------|------|-------|-------|
| Tin Plating (dB/m) | -0.90 | -1.4 | -2.2 | -4.0 | -7.5 | -10.9 | -14.6 |
| Silver Plating (dB/m) | -0.85 | -1.2 | -1.7 | -3.2 | -4.9 | -6.8 | -8.8 |

Mechanical Properties

| | |
|---------------------------|------------------------|
| Minimum Bend Radius | 1.0 mm (one-time fold) |
|---------------------------|------------------------|



RoHS Compliance Statement

"RoHS compliant" means that the product or part does not contain any of the following substances in excess of the following maximum concentration values in any homogeneous material, unless the substance is in an application that is exempt under RoHS: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers (including decaBDE); or (b) 0.01% (by weight) for cadmium.

Halogen Free Compliance Statement

Halogen-free is defined as both (1) no halogen compounds are intentionally added to the product or used in the manufacturing process for the product, and (2) any impurities present are less than 900 ppm bromine, less than 900 ppm chlorine, and/or less than 1500 ppm total bromine and chlorine. The latter are the levels set forth in certain industry standards for printed circuit boards, such as the International Electrotechnical Commission (IEC) 61249-2-21 standard.

Unless otherwise stated by 3M in writing, this information represents 3M's knowledge and belief based on information provided by third party suppliers to 3M.

Important Notice

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability

3M's product warranty is for one (1) year from the date of manufacture. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**

